

REQUIREMENTS

1. No work under this application is to be started until application is approved and the permit issued.
2. Property owner shall be responsible for all maintenance and liability in connection with the installed extension/connection. This includes the clearing of any pluggage within the extension/connection and the associated county culverts.
3. Where work on traveled roadway is necessary, traffic must be protected, and flags, flares and proper barricades must be placed in accordance with the standards of Minnesota Department of Highways.
4. No foreign material such as dirt, gravel, or bituminous material shall be left or deposited on the road during the construction of extension/connection or installation of drainage facilities. Roadside must be cleaned up after work is completed
5. Existing county culvert is not to be moved or changed. (Affected aprons shall be removed and the appropriate bands used for connection to the extension/connection)
6. Inspection by county personnel is required following placement of extension/connection pipe prior to back-filling and again when work has been completed and is ready for final inspection.
7. No changes or alterations in entrances may be made at any time without written permission from the Dodge County Highway Department
8. All culvert extensions or connections shall be the same inside diameter as existing culverts.
9. If perforated pipe is used it shall be filter wrapped.
10. A minimum of 6 inches of aggregate base is required with a consistent drainable slope. All organic material is to be removed below the intended pipe location.
11. When connecting culverts between 2 entrances, a drop inlet is to be installed at the in-flow of the lower county culvert within each extension/connection section. The drop inlet shall be 6 inches in diameter for every 100 feet of extension with a minimum of 12 inches diameter.
12. Approach grade of finished drive shall be no greater than 2% for a distance of 20' from edge of road.
13. Drive fill slopes shall be constructed 1:6 (1' vertical to 6' horizontal) and shall be hand finished and seeded.
14. Material for fill must be good clean material and free of foreign materials and debris.
15. If Dodge County shall make any improvements or changes on all or any part of it's R/W upon, over, under or along the C.S.A.H., C.A.R. or County Municipal Street then and in every case the applicant herein named shall, after notice from the County Engineer, proceed to alter, change, vacate or remove from Highway R/W said works necessary to conform with said changes without cost whatsoever to Dodge County.

CULVERT EXTENSION/CONNECTION PERMIT: Keep top of driveway 32 feet or less.

Permission is hereby granted for the construction of the driveway culvert extension/connection as described in the application. Said extension/connection to be constructed in accordance with the Dodge County Highway Regulations and subject to the above requirements and the following special provisions:

All work to be completed within 30 calendar days. In the event that the construction has not been completed by this date, this permit becomes null and void, the culvert reclaimed and the fee refunded.

_____ " Spiral X _____/Ft. @ \$ _____/Ft. C.S. Culvert = \$ _____ **Total Spiral Culvert**

_____ " Riveted X _____/FT. @ \$ _____/Ft. C.S. Culvert = \$ _____ **Total Riveted Culvert**

_____ Aprons @ \$ _____/Each = \$ _____ **Apron Total** _____ Bands @ \$ _____/Each = \$ _____ **Band Total**

\$ _____ **Culvert Grand Total**

Gravel Needed:

(_____ ft X .50 ft X _____ ft ÷ 27) X 1.3 = _____ yd³ X \$19.52 = \$ _____ **Cost of Gravel**
Width of Drive X Min. thickness X Length Gravel per cu. Yd.

Sub-Total \$ _____

6.875% Tax \$ _____

PERMIT FEE \$ 50.00

Grand Total Due: \$ _____